

VEHICLE BODY FRAME FOR MOTORCYCLE
AND ITS FABRICATION METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a vehicle body frame for a motorcycle and a fabrication method for manufacturing the same.

Description of Background Art

With reference to Fig. 7, a perspective view is illustrated of a representative vehicle body frame for a motorcycle. The frame 100 for a motorcycle is integrated by welding and includes a head pipe 101, upper longitudinal pipes 102, lower longitudinal pipes 103 (one of the pipes 103 is not illustrated), pivot plates 104 and a cross pipe 105.

Fig. 8 is a conventional flow diagram for fabricating a vehicle body frame and the designation STXXX is utilized to designate a particular step number.

ST111: The head pipe is fabricated by a gravity die casting process. The gravity die casting process is also simply referred to as a die casting process and is a

fabrication method in which a metal mold is used in place of a sand mold, molten aluminum is injected into the metal mold and a feeding head is applied thereon. Only gravity is utilized on the molten metal and a metal mold is used. Accordingly, the process is also referred to as "gravity die casting." Since the molten metal comprises
5 aluminum, for several tens of thousands of times it is feasible for supplying the molten metal injection into a metal mold made of gray cast iron (FC) or structural carbon steel. The cost of the mold can be reduced as compared with a sand mold.

The gravity die casting is preferably adopted for parts of a motorcycle having more or less complicated shapes because gases are not entrapped and the casting
10 surface is excellent since the injection speed is slow.

ST112: By projecting shot grains onto or buffing a provided head pipe cast article, the surface is finished.

ST113: Similar to ST111, the pivot plates are fabricated by the gravity die casting process.

15 ST114: By projecting shot grains onto or buffing provided pivot plates cast articles, the surfaces are finished.

ST115: Upper/lower longitudinal pipes as well as the cross pipe are fabricated by drawing or extrusion. Pipes or bars having uniform sections can be fabricated by drawing or extrusion swiftly and in mass production.

20 ST116: The upper/lower longitudinal pipes and the cross pipe are suitably cut and subjected to bending.

ST117: The above-described head pipes, upper/lower longitudinal pipes, pivot plates and cross pipe are integrated by welding.

ST118: The product is subjected to alumite treatment and an anodic oxidation coating is formed on the surface. Thereby, a beautiful vehicle body frame can be
5 fabricated.

However, according to the gravity die casting, as mentioned above, the injection speed is slow and accordingly, the productivity is low which hinders a reduction in fabrication cost of the vehicle body frame.

OBJECTS AND SUMMARY OF THE INVENTION

10 Hence, it is an object of the present invention to achieve a reduction in fabrication cost of the vehicle body frame by improving the constitution and the fabrication method.

According to the present invention, a vehicle body frame for a motorcycle is constituted of integrating pipes made of aluminum and a plurality of aluminum cast
15 parts by welding. The portions or the total of the plurality of aluminum cast parts are die cast products.

A die cast product is excellent in the production efficiency, resulting in achieving low cost of a cast product. Hence, by making the die cast products portions of constituent parts, the fabrication cost of a vehicle body frame is reduced.

20 According to the present invention, a vehicle body frame for a motorcycle is fabricated by the steps of integrating aluminum series die cast products and aluminum

series non-die cast products fabricated by a method other than die casting, subjecting an integrated article to an alumite treating and coating only die cast portions.

A state of the skin is deteriorated in a die cast product in comparison with a non-die cast product. Therefore, when alumite treating is completed, a die cast portion of an alumite coating does not have as good an appearance as compared with other portion thereof. Hence, the appearance of the vehicle body frame is maintained by coating only the die cast portion.

Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention, and wherein:

Figure 1 is an exploded view of a vehicle body frame for a motorcycle according to the present invention;

Figure 2 is a fabrication flow diagram of a vehicle body frame for a motorcycle according to the present invention;

Figure 3 illustrates views showing the vehicle body frame according to the present invention;

Figure 4 is a graph investigating a relationship between gate speed and a material gas amount;

5 Figure 5 is a graph showing a relationship between the gate speed and proof strength;

Figure 6 is a graph showing a relationship between the gate speed and tensile strength;

10 Figure 7 is a perspective view of a representative vehicle body frame for a motorcycle; and

Figure 8 is a fabrication flow diagram of a conventional vehicle body frame.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An explanation will be given as follows of an embodiment of the present invention in reference to attached drawings. Fig. 1 is a disassembled view of a vehicle
15 body frame for a motorcycle according to the present invention. The vehicle body frame 10 for a motorcycle comprises a head pipe 11, upper longitudinal pipes 12, lower longitudinal pipes 13, pivot plates 14 and a cross pipe 15.

Fig. 2 is a fabrication flow diagram of the vehicle body frame for a motorcycle according to the present invention and STXX designates a step number.

20 Further, the method of fabricating the head pipe, the upper/lower longitudinal pipes and the cross pipe is the same as described in the conventional technology and a special devise is needed in the method of fabricating the pivot plates.

STO1: The head pipe is fabricated by the gravity die casting process. Although an explanation of the gravity die casting process will be omitted since a detailed explanation thereof has been given in a description of the conventional technology, gases are not entrapped and the casting surface becomes excellent since the injection speed is slow.

STO2: By projecting shot grains onto or buffing the provided head pipe cast article, the surface is finished.

STO3: The upper/lower longitudinal pipes and the cross pipe are fabricated by drawing or extrusion. Pipes or bars having uniform sections can be fabricated by drawing or extrusion swiftly and in mass production.

STO4: The upper/lower longitudinal pipes and the cross pipe are suitably cut and subjected to bending.

STO5: The pivot plates are fabricated by a die cast casting method, described later. The die cast casting method is a fabrication method in which molten aluminum is injected into a cavity under high pressure. Accordingly, the production efficiency is excellent and a large amount of cast products can be fabricated at a low cost.

STO6: By projecting shot grains onto or buffing the provided pivot plate cast articles, the surfaces are finished.

STO7: The above-described head pipe, upper/lower longitudinal pipes, pivot plates and cross pipe are integrated by welding.

STO8: The product is subjected to the alumite treatment and an anodic oxide film is formed on the surface.

ST 09: Only the pivot plates are subjected to coating, mentioned later. Thereby, a beautiful vehicle body frame can be fabricated.

Figs. 3 (a) and 3 (b) are views showing the vehicle body frame according to the present invention.

5 Fig. 3 (a) shows the vehicle body frame 10 after the ST08 (alumite treatment), showing that the brightness and appearance differ at the pivot plates 14 in comparison with other portions (head pipe 11, longitudinal pipes 12, 13 and cross pipe 15).

10 Fig. 3 (b) shows the vehicle body frame 10 after the ST09 (local coating treatment), showing that the color of the pivot plates 14 looks like the color of other portions (head pipe 11, longitudinal pipes 12, 13 and cross pipe 15).

A detailed explanation will be given of die casting and coating which are features of the present invention.

15 In the die casting, the casting speed is extraordinarily higher than those of sand mold casting and metal mold casting. Accordingly, entrapping of gasses is significant, resulting in the roughening of the casting surface, and the entrapped gases remain in the form of air bubbles, resulting in the air bubbles are broken by welding heat.

Hence, there is carried out an experiment to establish a die casting method adaptable to the present invention as a premise of completing the present invention.

Experimental conditions:

20 (1) Composition of test sample; aluminum alloy die cast 6 series (JIS H 5302)

[Table 1]

Chemical symbol	Chemical components								
		Cu	Mg	Zn	Fe	Mn	Ni	Sn	Al
ADC6	0.1 or less	1.0 or less	2.5 -4.0	0.4 or less	0.8 or less	0.4 -0.6	0.1 or less	0.1 or less	balance

(2) Injection temperature; 730°C

(3) Caster; ordinary die casting machine

(4) Gate speed; 5-65 m/s

(5) Gate sectional area; 9.75 cm²

5 Fig. 4 is a graph illustrating a relationship between gate speed and a material gas amount in which a gas amount in a material (cast product) is illustrated by changing the gate speed in the experiment. The abscissa designates the gate speed and the ordinate designates the gas amount per 100g of aluminum.

10 According to the graph, it is known that when the gate speed exceeds 15m/s, the gas amount rapidly increases.

Fig. 5 is a graph showing a relationship between the gate speed and proof strength and Fig. 6 is a graph showing a relationship between the gate speed and tensile strength.

15 It is known that as has been explained in reference to Fig. 4, when the gate speed exceeds 15m/s, the gas amount increases rapidly and therefore, the gases remains as air bubbles. When the gate speed exceeds 15m/s in Fig. 5 and Fig. 6, both the proof strength and the tensile strength are remarkably reduced.

It is known from the explanation that in the aluminum alloy die casting, by restraining the gate speed to 15m/s, entrapping of gasses can significantly be reduced. It is prospected that if gasses are not entrapped, the casting surface becomes fine compared with that of a conventional die cast product and the invented die cast product can be welded since there are no air bubbles.

Further, although detailed data will be omitted, when the gate speed becomes lower than 5m/s, molten metal is cooled in a procedure of being filled in the cavity, resulting in a short run when molding.

Hence, it is preferable to set the gate speed to 5-15m/s.

Next, an explanation will be given of coating.

There is adopted a coating whose color is the same as that of alumite coating when the coating is dried and providing a cross linked coating dried at room temperature. In the case of "cross linked coating" the coating strength is large and therefore, there is no concern of peeling of the coating. Further, since "normal temperature drying" is carried out, heated drying is not needed. If the heated drying is carried out, the alumite coating is impaired. Because the heated drying is not needed, a number of coating steps can be reduced and an increase in the fabrication cost can be restrained.

Accordingly, the cross linked coating dried at room temperature is carried out in order to achieve protection of alumite and maintenance of coating.

Further, the aluminum cast parts according to the present invention are the head pipe and the pivot plates according to the embodiment and the die cast products

among them are the pivot plates. However, the present invention is not limited to this example, but the aluminum cast parts and the die cast articles may be any of members constituting the vehicle body frame for a motorcycle.

5 The aluminum series die cast products according to the present invention are the pivot plates according to the embodiment and the aluminum series non-die cast products are the head pipe, the longitudinal pipes and the cross pipe. However, the present invention is not limited to this example, but the aluminum series die cast products may be any of members constituting the vehicle body frame for a motorcycle.

10 Further, the longitudinal pipes or the cross pipe may be provided with any of a round section, a rectangular section or other noncircular section.

Further, aluminum here includes aluminum alloy.

The present invention achieves the following effects by the above-described constitution.

15 According to the present invention, in a vehicle body frame for a motorcycle including integrating pipes made of aluminum and a plurality of aluminum cast parts by welding, portions or a total of the plurality of aluminum cast parts are die cast products. Since the die cast products are provided with excellent production efficiency, a low cost of die cast products can be achieved. By making the die cast products portions of constituent parts, a reduction in the fabrication cost of the vehicle
20 body frame can be achieved.

According to the present invention, coating die cast portions are adopted in portions of the vehicle body frame. After the alumite treatment, the die cast portions of

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---